



深圳市拓湃新能源科技有限公司
Topak power Technology Co., Ltd

MATERIAL SAFETY DATA SHEET

1. Identification

Product name: Lithium Ion Battery

Model: 18650-7S4P

Voltage: 25.55V

Capacity: 10Ah

Edition date: 2019-01-11

Report No.: 23820190111A

Company: Topak POWER Technology Co., Ltd

Contact for information: 5 Building 1 unit. 502, Puhua Industrial Park, Gongyeyuan Road, Tongsheng Community, Dalang Street, Longhua New District, Shenzhen City, Guangdong Province, P.R. China

Emergency telephone No.: 0086-755-33940892

2. Ingredients

Chemical Composition	Molecular Formula	Weight%	CAS No	OSHA (PEL)	ACGIH (TLV)
Cobalt Compound	CoO	4~50%	1307-96-6	N/A	N/A
Polyvinylidene fluoride (PVDF)	(C ₂ H ₂ F ₂) _n	< 5%	24937-79-9	N/A	N/A
Carbon	C	10~30%	7440-44-0	N/A	N/A
Electrolyte	---	10~30%	96-49-1	N/A	N/A
Manganese Compound	MnO ₂	0~15%	1313-13-9	N/A	N/A
Copper foil	Cu	2~10%	7440-50-8	N/A	N/A
Nickel Compound	NiO	0~25%	1313-99-1	N/A	N/A
Styrene-Butadiene Rubber (SBR)	C ₁₂ H ₁₄	< 1%	9003-55-8	N/A	N/A
Lithium Hexafluorophosphate	LiPF ₆	< 5%	21324-40-3	N/A	N/A
Aluminum foil	Al	2~10%	7429-90-5	N/A	N/A

3. Hazards identification

Health Hazards (Acute and Chronic):

For the battery cell, chemical materials are stored in a hermetically sealed aluminum laminate case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.



扫描全能王 创建



深圳市拓湃新能源科技有限公司

Topak power Technology Co., Ltd

However, if exposed to a fire, added mechanical shocks, decomposed, or added electric stress by misuse the cell case will be breached and hazardous materials may be released. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

Carcinogenicity:

NTP: None IARC Monograph: None OSHA Regulated: None

Medical Conditions Generally Aggravated by Exposure:

An acute exposure will not generally aggravate any medical condition. Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.

Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and the stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and the stimulation on the eye. Inflammation of the eyes may occur.

Environmental effects:

Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards:

If the electrolyte contacts with water, it may generate detrimental hydrogen fluoride. Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

4. First aid measures

After inhalation contact: Make the victim blow his/her nose, gargle. Seek medical attention if necessary.

After skin contact: Remove contaminated clothes and shoes immediately. Immediately wash extraneous matter or contact region with soap and plenty of water.

After eye contact: Do not rub eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention.

After ingestion contact: Make the victim vomit. Immediately seek medical attention.

5. Fire-fighting measures

Extinguishing Media: Plenty of water, CO₂ gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.

Specific methods of simultaneously: When the battery burns with other combustibles fire-fighting: take fire extinguishing method which corresponds to the



扫描全能王 创建



深圳市拓湃新能源科技有限公司

Topak power Technology Co., Ltd

combustibles. Extinguish a fire from the windward as much as possible.
Flammable Limits: Not available

6. Accidental release measures

The preferred response is to leave the area and allow the batteries to cool and the vapors to dissipate. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

7. Handling and storage

Handle with care. Flammability hazard exists if the package is damaged. Before shipping, must to check out the package is damaged or not by inspection, if package damaged, must to be repacking. Avoid mechanical or electrical abuse. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection

Specific control parameter:

Personal protective equipment :

Respiratory protection (Specify Type):	Not necessary under conditions of normal use.
Ventilation:	Not necessary under conditions of normal use.
Protective Gloves:	Not necessary under conditions of normal use.
Eye protection:	Not necessary under conditions of normal use.
Other Protective : (Clothing or Equipment):	Not necessary under conditions of normal use

9. Physical and chemical properties

Appearance

Physical state:	Solid
Form:	Prismatic (Laminated)
Color:	Metallic color
Odor:	No odor
PH	N/A
Specific temperatures	Temperature ranges changes in physical state occur. Flash point
N/A	
Explosion properties	N/A
Density	N/A
Solubility	with indication of the solvent(s): Insoluble in water



扫描全能王 创建



深圳市拓湃新能源科技有限公司

Topak power Technology Co., Ltd

10. Stability and reactivity

Stability: Stable

Conditions to Avoid: When cell is exposed to an external short-circuit, crushes, deformation, high temperature above 100 degree C, it will cause heat generation and ignition. Avoid direct sunlight and high humidity.

Hazardous Decomposition: Acid or harmful gas is emitted during fire.

or By-products:

Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous will not occur.

11. Toxicological information

Acute toxicity:

Copper: 60-100mg sized coarse particulate causes a gastrointestinal disturbance with nausea and inflammation. TDLo, hypodermic - Rabbit 375mg/kg

Organic electrolyte: LD50, oral - Rat 2,000mg/kg or more

Further toxicological information:

Aluminum: By the long-term inhalation of coarse particulate or fume, it is possible to cause lung damage (aluminum lungs).

Lithium Cobaltate: By the long-term inhalation of coarse particulate or vapor of cobalt, it is possible to cause the serious respiratory-organs disease. Skin reaction or a lung disease for allergic or hypersensitive person may be caused.

Graphite: Long-term inhalation of high levels of graphite coarse particulate may cause lung disease or a tracheal disease.

12. Ecological information

Ecotoxic effects : N/A

Further ecological data: N/A

13. Disposal considerations

Topak POWER encourages battery recycling. Our Li-ion batteries are recyclable through the Rechargeable Battery Recycling Corporation's (RBRC) Charge Up to Recycle Program. For information call 1-800-8-BATTERY or see their website at www.rbrc.org. Li-ion batteries must be handled in accordance with all applicable state and federal laws and regulations.

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212°F. Such treatment can vaporize the liquid electrolyte causing cell rupture. Do not use in combination with fresh and used lithium batteries neither with other type of battery.



扫描全能王 创建



深圳市拓湃新能源科技有限公司

Topak power Technology Co., Ltd

14. Transport information

International transport regulations:

1. U.S. hazardous materials regulations pursuant to 49 CFR 173.185(b),
 2. 2019 IATA Dangerous Goods Regulations 60th edition.
 3. IMDG Code pursuant to Special Provision 188. 49 CFR 173.185(b)
- UN-No.: 3480&3481

Each Topak POWER cell or battery complies with the current edition –60th 2019 of IATA regulation:

- 1) Section II of Packing Instruction
PI965~PI967, For Li-ion cells or batteries, or packed with equipment, or contained in equipment.
- 2) UN manual of Tests and Criteria, Part III, sub-section 38.3 (withstanding a 1.2m drop test);
- 3) For cells with content of lithium is no more than 20 Wh, for batteries with content of lithium is no more than 100Wh per battery. The watt-hour rating must be marked on outside of the battery case.

If Topak POWER Li-ion cells are used to construct battery packs, the assembler of that pack is responsible to ensure the battery has been tested in accordance with the requirements contained in the UN Manual of Tests and Criteria and shipped in accordance with applicable regulations.

Batteries must be packaged and offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals) and protects against short circuits.

15. Regulatory information

N/A

16. Other Information

This information is not effective to all the batteries manufactured by Topak power. This information comes from reliable sources, but no warranty is made to the completeness and accuracy of information contained. Topak power doesn't assume responsibility for any damage or loss because of misuse of batteries. Users should grasp the correct use method and be responsible for the use of batteries.

NOTICE: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Topak power Technology Co., Ltd makes no warranty expressed or implied.



扫描全能王 创建